

LFMH

Classified Medium Flood

CLASS I DIVISION 2




- Decorative “Southwest” styling
- Low copper alloy, die-cast aluminum housing and door
- Tempered, impact-resistant clear glass lens
- Robust steel mounting yoke is standard
- Wide, uniform beam from one-piece hydro-formed reflector with coverage four times set back distance
- Energy-efficient pulse start and HPS ballast systems available
- Standard finish is bronze
- UL 844 listed, Class I, Division 2, Groups A, B, C, D
- UL 1598A Marine listed; NEMA 4X; IP66; Suitable for operation in ambient temperature up to 40°C
- Pulse-rated mogul socket standard

ORDERING INFORMATION

SERIES	MOUNTING	WATTAGE/SOURCE	VOLTAGE	FINISH	OPTIONS
LFMH Hazardous Location Flood	Y Yoke	PULSE START METAL HALIDE 150P 150w 250P 250w 320P 320w 400P 400w HIGH PRESSURE SODIUM 150S 150w 250S 250w 400S 400w	V 5 Tap (250, 400w HPS only) 8 Quad - Tap® (120, 208, 240, 277V) 5 480V E 220/240V, 50Hz 6 347V Canada	BZ Bronze	P(X) ¹ Button photocontrol F(X) ¹ Fusing LP Lamp included

T-CODE RATINGS	
Wattage & Lamp type	40° C Class I, Division 2
150 PSMH	T1
250 PSMH	T1
320 PSMH	T1
400 PSMH	T1
150 HPS	T2A
250 HPS	T1
400 HPS	T1

1 Replace (X) with correct voltage code: 1 = 120V, 2 = 208V, 3 = 240V, 4 = 277V, 5 = 480V, 6 = 347V



A	B	C	D	E	F	G	H
17.38"	18.58"	4.25"	2.50"	5.68"	.531"	.875"	3.125"
441 mm	471 mm	108 mm	63 mm	144 mm	13 mm	22 mm	79 mm



Industrial Lighting