

SWD/SWW HID

Superwatt®

ACRYLIC



- Superwatt luminaire is designed to provide illumination on vertical as well as horizontal surfaces
- The exclusive computer designed refractor has 95% efficiency
- 27% upright and greatly reduced glare
- 2.2:1 spacing to mounting height
- 27% upright softens the brightness difference between luminaire and surrounding areas
- The maximum downward candlepower is projected at 45° from vertical for wide distribution and the greatly reduced candlepower above 65° minimizes direct glare
- Superwatt luminaire is shipped in one carton, wired, with lamp installed and ready to hang
- SWW Series offers optional NSF certification to NSF Standard C-2 (-FP, shown below)
- Up to 55° ambient with "-HA" option

ORDERING INFORMATION



SW	-		-		-		-		-	
SERIES		SOURCE		REFRACTOR		MOUNT		OPTIONS		
SW ¹ Superwatt® Enclosed HID		S ⁵ High Pressure Sodium P Pulse Start Metal Halide EB ⁵ Electronic Ballast		A Acrylic P ⁶ Polycarbonate		P Pendant mount C ² Ceiling mount		F(X) ⁴ Fusing HA 55°C listing (250w only) CXHLPX ^{3,4} Cord, Hook/Loop, and 20A plug, DL only CHL 2' exposed Cord Hook/Loop QSS Quartz standby includes 150w lamp QST Quartz time delay, includes 150w lamp LL Less lamp S Screw down refractor EM Emergency quartz lamp socket FP National Sanitation Foundation Listed		
LISTING		WATTAGE		VOLTAGE		COLOR				
D Damp location W Wet location		200 200w PSMH only 250 250w PSMH, HPS, Electronic 320 320w PSMH, Electronic 350 350w PSMH, Electronic 400 400w PSMH, HPS, Electronic		2 208V 3 240V 5 480V 6 Tri-Tap® (120, 277, 347V) 8 Quad Tap® (120, 208, 240, 277V)		WH White (standard) GR Gray				

ACCESSORIES - Order Separately

Catalog Number	Description
SW-WG	Wireguard with safety chain.

- 1 Includes factory installed lamp
- 2 Surface mounting units for mounting on concrete and steel only
- 3 For cord length, replace first "X" with 2, 4, 6, 8, 10 or 12
- 4 For voltage, replace second "X" with 1=120V, 2=277V, 3=240V, 4=277V, 5=480V, 6=347V
- 5 EB is 120-277V, no voltage selection required
- 6 Polycarbonate only available with HPS

For a complete list of Options and Accessories see page 436 to 445.



PENDANT MOUNT

A	B	C	D	E
13 1/8"	22 1/2"	10 1/4"	11 9/16"	17 7/8"
333 mm	572 mm	260 mm	294 mm	454 mm

SURFACE MOUNT

A	B	C
24 1/4"	6 15/16"	17 7/8"
616 mm	176 mm	454 mm



Industrial Lighting